

PhoneLink®

厦门锋联信息技术有限公司

Phonelink Technologies (Xiamen) Co., Ltd.

Any Time ,Any Way 随时随地 + 传您所想
YOUR OFFICE MOBILE BY PHONELINK

地址：厦门市软件园望海路65号A栋5层 + 传真：0592-5962158

电话：0592-5038116 / 5112282 + Http://www.phonelink.com.cn

E-mail: phonelink@phonelink.com.cn + 邮编：361008

PLK-TF-06G

Made in Xiamen

GSM Portable Fax



- * Thermal paper up to A4
- * Group3 analog fax CLASS 1&2
- * GSM/PSTN dual mode
- * GSM SMS printed
- * Copier
- * LCD display call ID
- * No-paper capacity 40 pages
- * Vehicle adapter power
- * PC Scanner and printer
- * WCDMA router with WIFI/LAN (06+)

Lost The Line, Mobile Your Office.

More:

- * Mobile and fixed easily
- * Fax/Voice/auto mode
- * GSM/PSTN auto switch
- * Small volume & weight
- * 220V adapter is standard
- * 12/24V vehicle adapter is standard
- * For car, ship, mobile house
- And portable design
- * Be fixed on vertical plane
- Easily.

Working in:

GSM/GPRS/EDGE

* 900/1800MHZ GSM Phase 2+

* 850/900/1800/1900MHZ

PSTN

SATELLITE Terminal connected

PLK-TF-06G

GSM portable fax

Feature

- * GSM G3 analog fax class 1&2
- * PSTN fax and telephone
- * Copier
- * GSM telephone call
- * A4 thermal paper
- * No-paper received capacity to 40 pages
- * Special design power for vehicle
- * Mount and mobile easily
- * Standard GSM mini SIM card

Outside accessory

AC Adapter power

Input: 220v 50/60Hz

Output: 24v 2.0A

Vehicle power supply

Input: 12/24V

Output: 24V 2.0A

OPTIONAL:

Special antenna

Emergency backup battery

Special fixed packet for fax and pc

In vehicle

PhoneLink 锋联™

Model: Support GSM G3 analog fax and

PSTN /SATELLITE

- * 900/1800 GSM Phase 2+
- * 850/900/1800/1900 GSM Phase 2+
- * PSTN
- * SATELLITE

Specification

GSM air interface standard

- * GSM 850/900/1800 Phase 2+
- * PCS 1900 TIA/EIA J-STD-007 PCS 1900

Transmit Power

- * EGSM 900: 2W * DCS1800/PCS1900: 1W

Frequency Ranges

- | | |
|------------------------|--------------|
| * GSM850 824-849MHZ | 869-894MHZ |
| * EGSM900 890-915MHz | 935-960MHz |
| * DCS1800 1710-1785MHZ | 1805-1880MHz |
| * PCS1900 1850-1910MHZ | 1930-1990MHz |

Dimensions and Weight

- * 288 x 188 x 96mm
- * Less 1.6kg

Environment

- * Operating temperature range:-10°C to +50°C
- * Storage temperature range -40°C to +60°C
- * Humidity: 5% to 95%

Antenna

- GSM 900/1800: 3dBi dual band
- GSM 850/1900: 3dBi dual band
- Optional higher gain antennas available

SCAN: Contactor Image Sensor

Level: 8PPM

VER: 7.7RPM (fine) 3.85RPM (standard)

Printer: Thermal

Printer width: 210/216MM*30MM

Fax DCS: MH、MR、H2